





BS-250S





BS-250SSV

HORIZONTAL BAND SAW

SPECIFICATION

Model	BS-250S	BS-1016SV	BS-250SSV
Capacity	90° ● 260 mm	■ 260 mm	— 420 x 180 mm
	45° ● 260 mm	■ 260 mm	— 295 x 260 mm
Blade Size	27 x 0.9 x 3430 (mm)		
Blade Speed	25, 40, 51, 71 MPM	30 ~ 106 MPM	25 ~ 75 MPM
Blade Motor	2 HP		
Packing Size (CRT)	1940x 750 x 1190 mm (L x W x H)	1940x 750 x 1210 mm (L x W x H)	1940x 750 x 1190 mm (L x W x H)
N.W / G.W	420 kgs / 480 kgs	440 kgs / 500 kgs	460 kgs / 520 kgs
Container Loads	18 units / 20' \ 36 units / 40'		

FEATURES:

- * Heavy duty cast iron construction.
- * Blade chip brush, safe guards.
- * Low voltage control with overload protection.
- * Efficient coolant system with built-in tank and pump.
- * Smooth and silent in operation.
- * Carbide tunasten guide and bridge type portal frame.
- * Easy blade change . Adjustable tension . Rigid and precise blade guides.
- * Centralised controls to avoid operator fatigue.
- * Main components and table made by FC-25 and FC-45 quality cast iron.
- * Stop bar as guide to cut premeasured cutting length, It adjusts to angle cutting of 0-45 degree.
- * Angle setting is simple, Operation is easy.
- * For sawing an angle, the material may stay numoved. Work efficiency is high.

STANDARD ACCESSORIES:

- * One saw belt (installed on the machine)
- * A semicircle liquid collecting board , 1 piece
- * Adjusting tools and tool box , 1 set
- * Material of fixed size , 1 set



SAWTECH MACHINE INC.

7 Chuang Chien Road, Shen Kang Village, Taichung County (429), Taiwan.

TEL: +886 - 4 - 25628131 \ 25629579

FAX: +886 - 4 - 25629578 E-mail: dingho@ms55.hinet.net Website: http://www.sawtech.com.tw